

H.264 (Original)

AS-408SR



บันทึกภาพด้วย Technology H.264

Support SATA HDD , มี VGA Port

ระบบ CMS ได้ถึง 36 กล้อง

DVD-RW(Optional)

Specifications

AScCTV

Item	Parameter	8-Channel
System	Operation system	Linux
	System resource	Multiplex: Liveview, Recording, Playback, Remote
	Input device	Mouse, Remote controller
Compression Standard	Video	H.264
Video Monitoring	VDO input	8-channel composite VDO (NTSC/PAL) BNC (1.0Vp-p,75Ω)
	VDO output	1-channel composite VDO (NTSC/PAL) BNC (1.0Vp-p,75Ω) 1-channel VGA output
	Video standard	PAL (625 lines, 50 fields/second), NTSC(225 lines, 60 fields/second)
	Partitioning screen	1, 4, 8, 9
	Image resolution	Real-time monitoring D1 704x576 / 704x480 visual recording playback CIF 352x288 / 352x240
	Image quality	Adjusted within 6 levels
Audio	Audio input	8-channel (RCA)
	Audio output	1-channel (RCA)
Hard disk	Hard disk	4 SATA interfaces can hitch 1-4 hard disks
Recording	Recording mode	Manual, Schedule, Motion detection, Alarm
	Recording time	File record time can be set from 5 to 120 minute
Playback & Search	Search mode	Time, Event
	Playback screen	1, 4
Backup	Backup method	Support USB memory devices, DVD-RW
Network	Ethernet	10/100 base-t
	DDNS	yes
	Network IP	Static, DHCP, PPPoE
	Multi remote client	กำหนดได้ 12 User และสามารถกำหนดสิทธิ์ต่างๆได้ สามารถ login พร้อมกันได้ 8 user
	Remote Display	Up to 36 channel
	Network mode	Setting DVR, สั่งปิดDVRได้, Live view, Playback, Control PTZ, CMS Update Firmware
Alarm	Alarm Input	8 In (NO/ NC)
	Alarm output	2 Out (NO/ NC)
	Motion detect area	16x12 (BOX)
	Motion detect sensitivity	Multi level
	VDO loss detect	Yes
	Alarm record	Yes
Other	Power supply	12DC, 6A
	Power consumption	20W-90W
	Application temperature	0° to 55°c
	Application humidity	10%-90%

