



MagiC H.264 (Original)

Specifications

DVR 16 CH

Model	MG-P164
Compression	H.264 / Pentaplex
Operating System	Embedded Linux
OS Firmware	Linux OS in Flash Memory
NTSC or PAL (Auto Selected)	Yes
Video Input	composite 16 BNC Inputs
Main Monitor Output	1 BNC / 1 VGA
Spot Output	1 BNC
Sequence	Yes
Resolution Frame Rate at CIF	480fps(NTSC)/400fps(PAL)
Resolution Frame Rate at H.D1	240fps(NTSC)/200fps(PAL)
Resolution Frame Rate Full D1	120fps(NTSC)/100fps(PAL)
Audio Input	1 Input (RCA jack)
Audio Output	1 Output (RCA jack)
Ethernnet / Network	10/100Mbps Ethernet (RJ-45)
Video Stream	Dual
Alarm Input	2 TTL, Programmable as NC/NO
Alarm Output	1 TTL, Programmable as NC/NO
USB Interface	2xUSB 2.0
Search	Date / Time / Calendar / Event
User Interface (GUI / Control Device)	Yes / Keyboard, Mouse, PTZ Control, Remote Controller
Archive File Format	EXE (Video Clip) / JPEG (Still Image)
Recording Qualities	Super/High/Standard
Recording Moods	Continuos/Alam/Motion/Emergency
Pre-ALAM Recording	Up to 3 Hours/User Programmable
Motion Detection	Yes (22z15)
Playback Speed	x1,x2,x4,x8,x16,x32,x64,Extreme
PTZ Control	RS-485/422 Serial Port 1 (Terminal Block)
Preset Touring	Yes
Multi Language	English/Danish/Chinese (Traditional)/ Japanese/Korean/Italian/Polish/Russian/Chinese (Simplified)/Thai/Turkish/Spanish/French/Czeco/German/Persian/Portugrese/Croatian
Primary Storage	SATA HDD 1
Clip Copy Storage	Built-in Internal DVD-RW, Memory
Operating Humidity	5°C - 40°C / 41°F - 104°F
Power Adaptor	Free Voltage 12VDC, 5A
Power Consumption	Max 14W
Agency Approval	FCC / CE